element

DESIGN. QUALITY. PURPOSE



Element 455W POS Terminal

Element 455W

Element 455W, 15.6" is an all-in-one POS Terminal, equipped with a VESA mount bracket in both the back cover and the stand. The aesthetic design of the chassis and the seamless integration of modular peripherals such as MSR, iButton, Fingerprint, Second Display and Customer Display make it the perfect unit for the retail, hospitality or digital signage industries where you need larger format displays to suit your applications.



Element 455W POS Terminal

Features

- 15.6" True-Flat PCAP multi-touch Display
- Intel Tiger Lake or Elkhart Lake Processor
- MSR/ iButton/ Fingerprint Available
- Fanless design with multiple CPU options
- 2nd Display and Customer Display Options (CDU) Available
- High Flexibility with Foldable Stand
- Modular design with blade peripherals
- Double Hinge foldable stand
- Multiple Vesa mounting options.
- Easy access to rich I/O's
- Intelligent cable management
- Standard 3-year warranty.



Element 455W POS Terminal

Sleek & Fashionable

The Element 455W is built with industrial grade components designed from the ground up to support a range of processors in an all-in-head design. The result a POS terminal designed to be sleek and fashionable, whilst providing the power, performance and reliability needed for varied POS applications.

- Designed for industrial and commercial applications.
- Uses the long-term roadmap of Intel embedded chip sets.
- Built for the modern needs of Retail and Hospitality.





*Optional Stand

Element 455W POS Terminal

Foldable Stand

- High Flexibility
- Double Hinge
- VESA mounting compatible for both back cover and foldable stand



element



Foldable Stand : 75 x 75mm & 100 x 100mm



Back cover : 100 x 100mm



Step 1.



Step 2.





Package Size & Cost are Lower

100 mm

Element 455W POS Terminal

Modular Design



element



Peripherals with Blade Connectivity

- High Interchangeability
- Easy Maintenance



iButton



3-Track MSR



Fingerprint

Element 455W POS Terminal

Connectivity



- 7. DC Jack
- 8. RJ45 LAN port
- 9. FeDP port (for 2nd display)
- 10. Powered USB 24V port (option)
- 11. Powered USB 12V port (option)

- 1. RJ11 Cash drawer port
- 2. DB9 COM port (2)
- 3. USB 3.0 port (2)
- 4. USB Type-C port (USB2.0 data only)
- 5. USB Type-C port (USB3.0 data only)
- 6. USB 2.0 port (2)

Element 455W POS Terminal

Summary

Applications			
Hospitality such as:			
Quick service restaurants			
• Pubs			
• Clubs			
• Cafes			
Fashion & Apparel			
Grocery			
Pharmacy			
Petroleum			
Digital Signage industry			
Industrial and Commercial			

Features

15.6" True-Flat PCAP multi-touch Display

Fanless design built for retail, reliable and robust

High Flexibility with Foldable Stand Double Hinge foldable stand

Elkhart Lake or Tigerlake Processor

2nd Display and Customer Display Options (CDU) Available

Modular design with blade peripherals - MSR/ iButton/ Fingerprint

Unique Selling Points

Sleek and fashionable

Powerful, performance and reliability driven needed for varied POS applications

Intelligent cable management

Easy access to rich I/O's


Multiple mounting & stand options

Built with industrial grade components designed from the ground up to support a range of processors in an allin-head design.

<u>SPECIFIC</u>ATIONS

System	Model Mathada and	455W F34	455W F84U
	Motherboard	F34 Intel® Elkhart Lake Celeron J6412 2.6 GHz	
	Processor		Intel® Tiger Lake i3-1115G4
	Memory Storage	4GB DDR4 (Max 32GB)	
	Size and Resolution	128GB SSD (M.2) 15.6" 1920×1080	
Display	Touch Screen	True-Flat PCAP multi-touch	
Expansion	Mini PCI-E Slot	1	
I/O Ports		2x USB3.0, 2x USB.3.0,	
	USB Type-A	2x USB2.0	2x USB2.0
	USB Type-C	1x USB.2.0 (data only) 1x USB 3.0 (data only)	1x USB 3.0 (data only) 1x USB 3.0 (full-featured)
	Serial Port	2x DB9 (default: 0V; COM1/COM2: 0V, 5V, 12V)	
	LAN	1x RJ45	
	Cash Drawer	1x RJ11 (12V/24V)	
	VGA	1 X Fedp port	
	DC Jack	1x 4PIN w/lock	
Optional I/O	Powered USB	1x Powered USB 12V, 1x Powered USB 24V	
·	RUSB	In display	
Audio	Internal Speaker	1x 3W (Option)	
Indicator	LED Speaker	1	
Power	Power Adapter	65W / 19V	120W / 19V
Communication	Wireless LAN + BT (Optional)	Wi-Fi + BT USB dongle (Option)	
	MSR	3-Track MSR (USB)	
	Fingerprint	Fingerprint reader (USB)	
Peripherals (Option)	iButton	iButton (USB)	
	Customer Display	LCM display 2 x 20 characters (USB)	
	2nd Display	11.6" 2nd display (optional)	
Certificate	EMC & Safety	FCC Class A, CE Mark, LVD	
Environment	Operating Temperature	0°C ~ 35°C (32°F ~ 95°F)	
	Storage Temp.	-20°C ~ 60°C (-4°F ~ 140°F)	
	Humidity	20% ~ 85% RH non-condensing	
Dimensions	W x D x H	15.6" 369 x 209 x 264 mm (14.5" x 8.2" x 10.4")	
Weight	Weight	4.3 kg (9.5 lbs)	
Mounting	VESA Mount	100 x 100	
OS Supported		Windows 10 IoT Enterprise Linux	
			V





eenent

www.elementpos.co